

# BLACK TIE MANUFACTURING, INC.

## Trailer Specifications | Optimum Models

### Guest Use Features Include

- Seal and low volume ceramic toilets with pedal flush
- Lavatory in vanity with mirror
- Porcelain sinks with metered water faucets (Units 12' and smaller have plastic sinks)
- Wall hung porcelain urinals with metered flush valve
- Six-gallon electric water heater (Units 14' and smaller have 2.5 gallon electric water heater)
- Air conditioning with heat strip

### Standard Equipment and Features Include:

- 4" x 10" structural steel main I-beam frame with rear bumper
- 7000 lb. axles with eight stud hubs and electric brakes; (6,000 lb axles and leaf springs on 12' and under)
- 1.5" x 1.5" x 11 gauge steel tubing floor joists; 16" o.c.
- 8,000 – 25,000 lb. tongue mounted frame jack
- 2 - 5/16 ball hitch
- Four 7,000 lb. leveling jacks (2000 lb. leveling jacks on units 12' and under)
- ST225/75/R15 LRD Tomax radial tires on trailers 12' and under
- ST235/80/R16 LRE Tomax radial tires on trailers 14' and larger
- One-piece 1" undercoated Adventech with Par max sub-flooring
- Single-piece seamless vinyl charcoal diamond floor covering
- .040 white Filon laminated fiberglass interior
- .045 TPO membrane roof with 10 year limited warranty
- .040 Pebbleboard ceiling with R13 insulation
- rating
- Pre-finished, smooth white entry/exit and mechanical room doors
- 2 x 6 wood entry/exit door frame
- 87" inside height with 16" o.c. vertical studs
- High-density polyethylene Partitions.
- Fluorescent light fixtures in restrooms and mechanical room
- 11,000 BTU roof mounted A/C unit(s) (9,000 BTU on units 12' and under)
- 20 amp panel boxes located in onboard locking mechanical room
- D.O.T. approved running lights
- Entry/Exit deck lighting
- Telescopic stairs with deck platform
- Stainless steel fold out support handrails
- Removable 1/2" copolymer waste tank with cleanout and dipstick and tank monitor
- City water hookup
- City sewer hookup with 3" banjo dump valve